

交連聚乙烯絕緣聚氯乙烯被覆電纜 (XLPE-PVC) 構造表

600V

	公稱 斷面積	最小平均 絕緣厚度	最小平均 被覆厚度	約計完成 外徑	交流試驗 電壓	20°C 最大導體 直流電阻	20°C 最小絕緣 電阻	約計 重量	標準 單長
	mm ²	mm	mm	mm	KV/5分	Ω /km	M Ω·km	kg/km	m
單 心	2.0	0.76	0.38	4.3	3.5	9.24	2500	51	300
	3.5	0.76	0.38	4.9	3.5	5.20	2000	71	300
	5.5	0.76	0.38	5.5	3.5	3.33	2000	94	300
	8	1.14	0.38	6.7	3.5	2.31	1500	134	300
	14	1.14	0.76	8.5	3.5	1.30	1500	203	300
	22	1.14	0.76	9.6	5.5	0.824	1500	288	300
	30	1.14	0.76	10.5	5.5	0.623	1000	358	300
	38	1.40	0.76	12.0	7.0	0.487	1000	450	300
	50	1.40	1.14	14.0	7.0	0.378	1000	566	300
	60	1.40	1.14	15.0	7.0	0.303	1000	679	300
	80	1.40	1.14	16.0	7.0	0.229	1000	869	300
	100	1.40	1.14	17.5	7.0	0.180	800	1083	300
	125	1.65	1.65	21.0	8.0	0.144	800	1396	300
	150	1.65	1.65	22.0	8.0	0.118	800	1676	300
	200	1.65	1.65	24.0	8.0	0.0922	800	2091	200
	250	1.65	1.65	26.0	8.0	0.0722	600	2665	200
	325	2.03	1.65	30.0	10.0	0.0565	600	3380	200
	400	2.03	1.65	32.0	10.0	0.0454	600	4147	200
	500	2.03	1.65	35.0	10.0	0.0373	600	4990	150
	600	2.41	2.41	41.0	10.0	0.0304	600	6105	150
800	2.41	2.41	46.0	10.0	0.0234	400	7883	150	
1000	2.41	2.41	51.0	10.0	0.0179	400	10160	150	
二 心	2.0	0.76	1.14	9.4	3.5	9.42	2500	116	300
	3.5	0.76	1.14	11.0	3.5	5.30	2000	160	300
	5.5	0.76	1.14	12.0	3.5	3.40	2000	213	300
	8	1.14	1.52	15.0	5.5	2.36	1500	341	300
	14	1.14	1.52	17.5	5.5	1.33	1500	502	300
	22	1.14	1.52	19.5	5.5	0.840	1500	699	300
	30	1.14	2.03	22.0	5.5	0.635	1000	917	300
	38	1.40	2.03	25.0	7.0	0.497	1000	927	300
	50	1.40	2.03	27.0	7.0	0.386	1000	1419	300
	60	1.40	2.03	29.0	7.0	0.309	1000	1683	300
	80	1.40	2.03	32.0	7.0	0.234	1000	2125	300
	100	1.40	2.03	35.0	7.0	0.184	800	2615	300
	125	1.65	2.03	39.0	8.0	0.147	800	3236	300
	150	1.65	2.03	42.0	8.0	0.120	800	4053	300
200	1.65	2.79	47.0	8.0	0.0940	800	5003	300	
250	1.65	2.79	52.0	8.0	0.0736	600	6313	200	
325	2.03	2.79	58.0	10.0	0.0576	600	7985	200	
三 心	2.0	0.76	1.14	9.9	3.5	9.42	2500	142	300
	3.5	0.76	1.14	11.5	3.5	5.30	2000	200	300
	5.5	0.76	1.14	12.5	3.5	3.40	2000	272	300
	8	1.14	1.52	16.0	5.5	2.36	1500	431	300
	14	1.14	1.52	18.5	5.5	1.33	1500	649	300
	22	1.14	2.03	22.0	5.5	0.840	1500	971	300
	30	1.14	2.03	24.0	5.5	0.635	1000	1220	300
	38	1.40	2.03	27.0	7.0	0.497	1000	1533	300
	50	1.40	2.03	29.0	7.0	0.386	1000	1914	300
	60	1.40	2.03	31.0	7.0	0.309	1000	2271	300
	80	1.40	2.03	34.0	7.0	0.234	1000	2908	300
	100	1.40	2.03	37.0	7.0	0.184	800	3604	300
	125	1.65	2.03	41.0	8.0	0.147	800	4643	300
	150	1.65	2.79	46.0	8.0	0.120	800	5560	300
200	1.65	2.79	50.0	8.0	0.0940	800	6907	200	
250	1.65	2.79	55.0	8.0	0.0736	600	8769	200	
325	2.03	2.79	62.0	10.0	0.0576	600	11120	200	
四 心	2.0	0.76	1.14	11.0	3.5	9.42	2500	174	300
	3.5	0.76	1.14	12.5	3.5	5.30	2000	252	300
	5.5	0.76	1.52	14.5	3.5	3.40	2000	373	300
	8	1.14	1.52	17.5	5.5	2.36	1500	545	300
	14	1.14	1.52	21.0	5.5	1.33	1500	885	300
	22	1.14	2.03	24.0	5.5	0.840	1500	1251	300
	30	1.14	2.03	26.0	5.5	0.635	1000	1554	300
	38	1.40	2.03	29.0	7.0	0.497	1000	1960	300
	50	1.40	2.03	32.0	7.0	0.386	1000	2457	300
	60	1.40	2.03	34.0	7.0	0.309	1000	2943	300
80	1.40	2.03	38.0	7.0	0.234	1000	3760	300	
100	1.40	2.79	43.0	7.0	0.184	800	4845	300	

註：本項產品係正字標記優良產品。